

Reolink-TrackMix-LTE-IP-Camera-Specifications

	Model	Reolink TrackMix LTE
Video & Audio	Image Sensor	1/3"CMOS Sensor
	Video Resolution	UP To: 2560 x 1440 (4.0 Megapixels) at 15 frames/sec
	Lens	f=2.8mm@F=1.6, f=8mm@F=1.6
	Video Format	H.264,H.265
	Field of View	Horizontal: 96°-38° Vertical: 55°-21°
	Zoom Mode	6X hybrid zoom
	Day & Night	IR-cut filter with auto-switching
	Infrared Night Vision	Up to 15 Meters (50ft)(LED: 2pcs/850nm)
	Color Night Vision	Spotlight: 1pcs/6500K/450 Lumens
Power	Audio	Two-way audio
	Battery	5100mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
	Solar	Reolink Solar Panel 2
Interface	DC Power	5V/2A
	Power	USB Type-C port
	System	Reset button
	Storage	Micro SD card slot (Max. 128GB)
	Network	Nano SIM card slot
Pan & Tilt	Audio	Built-in microphone and speaker
	Pan &Tilt	Pan: 355°, Tilt: 0°~90°; (Speed can be set)
	Preset	32
3G/4G	Auto Tracking	Support
	Frequency Bands	LTE FDD: B1/B3/B7/B8/B20/B28A
		WCDMA: B1/B8
		LTE FDD: B2/B4/B12
		WCDMA: B2/B4/B5
	Transmission Data	LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28
		LTE TDD: B40
		WCDMA: B1/B2/B5/B8
LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL)		
Software Features	LTE TDD: Max 8.96Mbps(DL), Max 3.1Mbps(UL)	
	HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL)	
	UMTS: Max 384Kbps(DL), Max 384Kbps(UL)	
	Frame Rate	Mainstream: 10fps - 15fps Substream: 10fps - 15fps
	Code Rate	Mainstream: 1024Kbps -4096Kbps Substream: 64Kbps -512Kbps
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	PIR detection/person detection/vehicle detection/pet detection
	Record Mode	Motion triggered recording
Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P	
Maximum User Access	Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)	
Work with	Google Assistant, Reolink Cloud	
Working Environment	Operating Temperature	-10°C~+55°C (14°F~131°F)
	Operating Humidity	20% ~ 85%
	Waterproof	Support
Size & Weight	Dimension	228.2*147*129mm
	Weight	1.4KG
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/