

Reolink-Go-PT-Ultra-IP-Camera-Specification		
	Model	Reolink Go PT Ultra
Video & Audio	Image Sensor	1/2.7" CMOS Sensor
	Video Resolution	3840 x 2160 (8 Megapixel)@15fps
	Video Format	H.265
	Field of View	Fixed Lens, Horizontal: 90°, Vertical: 47°, Diagonal: 110°
	Infrared Night Vision	Up to 10 Meters (33ft) (LED: 2pcs/1.2W/850nm)
	Color Night Vision	Spotlight: 2pcs/2.4W/6500K
Alarm	Audio	Two-Way Audio
	Smart Alarm	PIR Detection/Person Detection/Vehicle Detection/Pet Detection
	PIR Detecting Distance	Adjustable up to 10m (33 ft)
	PIR Detecting Angle	120° Horizontal
	Audio Alert	Customized Audio Alerts
Pan & Tilt	Recording	Motion-Triggered Recording
	Other Alerts	Instant Email Alerts and Push Notifications
	Pan & Tilt	355° Pan, 140° Tilt
3G/4G	Preset	Supports 1 guard position & up to 32 preset positions
	Frequency Bands	Europe Version: LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8
		USA Version: LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71
Australia Version: LTE FDD: B1/B3/B5/B7/B8/B28 WCDMA: B1/B5/B8		
Power	Battery	21.6Wh Rechargeable Battery (Battery life varies based on settings, usage & temperature)
	Solar	Reolink Solar Panel 2
	DC Power	USB Type-C port
Storage	Local Storage	Micro SD Card (32GB included, max. 128GB)
	Cloud Storage	Reolink Cloud (only available in some countries)
Smart Home	Smart Home	Google Assistant
Working Environment	Operating Temperature	-10 to 55° C (14° to 131° F)
	Weather Resistance	IP64
Size & Weight	Size	Φ98 x 122mm
	Weight (Battery included)	496g
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/